
FEATURES

3 frameless glass panels, of which 1 or 2 are operable
Accepts glass thicknesses from 6mm – 10.5mm, for double glazed options refer to the double glazed section
Optional fly or security screens
Adaptable to suit most commercial framing systems
Adaptable to suit flat timber framing systems
Lockable in closed and partially open position by a keyed or pin lock
Clear acrylic handles or optional aluminium lift rail

SPECIFICATION TEXT

Frame Types

Sashless Windows

Sashless windows to be manufactured by Austview Sashless Windows using the 3 panel sashless window system.

Sashless windows to include [aluminium / timber] guides [inside only / inside and out]

Timber guides to be [KDHW / Western Red Cedar] N/A for aluminium sashless windows

Sashless windows to be operated by [acrylic lift block / aluminium continuous lift rail]

Sashless windows [to include / not to include] [flyscreen / security screen]

Selected sashless windows to be engineered, manufactured and installed by Austview Sashless Windows or an equivalent and approved fabricator of Austview Sashless Windows.

To be engineered, manufactured and installed in accordance with:

AS 2047-2048 (windows in buildings)

AS/NZS 1170 (loading code)

AS/NZS 1664 (aluminium structures code)

Selected glazing (6mm-10mm)

Selected glazing to be in accordance with performance requirements as set out in AS 1288 (glass in buildings)

Finish: (Colour) [Powdercoat / Anodised] finish to aluminium

