

## HEAD, SILL AND JAMB 400 SERIES FRAMING NOTES: ALL BAL40 SEALS TO HAVE FLAMMABILITY INDEX OF 1.0 **Head Detail** 4 REMOVABLE FLYSCREEN LEG -OPTIONAL FLYSCREEN W/ S/S MESH AND BAL40 SPLINE BAL40 SEALS F0606 BAL40 GLAZING WEDGE 45 SELECTED TOUGHENED GLASS MINIMUM 6MM THICKNESS **Typical Elevation (internal) OUTSIDE** BAL40 GLAZING WEDGE BAL40 SEALS F0606 ALUMINIUM GLASS RAIL STANDARD LOCK POSITION OPTIONAL LOCK POSITION OPTIONAL LOCK POSITION 2 LOCKS REQUIRED FOR THIS OPTION & NO VENT LOCK AVAILABLE S/S BALL BEARING ROLLERS WATER DRAINAGE IJ CLIP-IN SILL SECTION 4 Sill Detail حيا ا 400 SERIES FRAMING Jamb Detail BAL40 SEAL F0709 **Glass Overlap Detail** 102 102 KEYED SATIN CHROME LOCK BONDED TO GLASS W/ UV GLUE BAL40 SEAL F0707 OUTSIDE ACRYLIC LOCK KEEPER BONDED TO GLASS W/ D/S TAPE FIRE RATED STOP 400 SERIES FRAMING POCKET FILLER (by others) BAL40 SEAL F0204





